

Thank you for visiting CarltonSales.com, part of the GrossAutomation.com family.

This document has been identified as being potentially out of date. It is therefore to be considered “for historical reference only” and not to be used for making current decisions.

Both Gross Automation, as the distribution channel, and Carlton, part of the Thomas & Betts family of ABB Installation Products, are happy to help you.

Gross Automation’s Global Sales

Department may be reached at +1 (262) 252-1600.

Carlton Technical support may be reached at +1 (888) 862-3289.

**TECHNICAL INFORMATION FOR CARFLEX[®] LIQUIDTIGHT FLEXIBLE
NONMETALLIC CONDUIT**

1. There shall be no more than the equivalent of four (4) quarter (90°) bends (360° total) between pull points, conduit bodies, and boxes.
2. The radius of the curve of the center of the conduit or tubing shall not be less than that shown in the table below:

SIZE OF CONDUIT OR TUBING		RADIUS TO CENTER OF CONDUIT OR TUBING	
Inches	Metric Desgr.	Inches	(mm)
3/8	(14)	4	(101.6)
1/2	(16)	4	(101.6)
3/4	(21)	4-1/2	(114.3)
1	(27)	5-3/4	(146.0)
1-1/4	(35)	7-3/4	(184.1)
1-1/2	(41)	8-3/4	(209.5)
2	(53)	9-1/2	(241.3)